

ENERGY STAR® Certified in Highlighted Regions



■ Certified



National Fenestration Rating Council®

CERTIFIED

8200-XO
PVC Frame - LOW E 366™
Laminated Double Glazed
ARGON/AIR
PEL-K-266-00672-00001
FL# 33554.1 / IG NAMI-10629

ENERGY PERFORMANCE RATINGS

U-Factor (U.S. / I-P)

0.30

Solar Heat Gain Coefficient

0.21

ADDITIONAL PERFORMANCE RATINGS

Visible Transmittance

0.48

-

Manufacturer stipulates that these ratings conform to applicable NFRC procedures for determining whole product performance. NFRC ratings are determined for a fixed set of environmental conditions and a specific product size. NFRC does not recommend any product and does not warrant the suitability of any product for any specific use. Consult manufacturer's literature for other product performance information.
www.nfrc.org

DESIGN PRESSURE

As Limited by All Components

+50

-50

Negative Design Pressure Limited by tested pressure and Glass Tables ASTM E1300-04.
 Positive Design Pressure Limited by water test pressure and Glass Tables ASTM E1300-004

Fixed: L2A-A 366/C 7/8" OA: (1/8" ANN-20/48" ARGON-5/16" LAMI[1/8" ANN-.090' PVB-1/8" ANN])

798,906.00.8.00.1.00.1.00 : pos 7.00

35-17740-1